



PS-02A	PS-02B	PS-02C
■ 1,4-2,8bar	■ 1,4-2,8bar	■ 1,4-2,8bar
■ 2,1-3,5bar	■ 2,1-3,5bar	■ female/male
■ 2,8-4,3bar	■ 2,8-4,3bar	
■ female/male	■ 3,5-5,6bar	
	■ 4,9-7,2bar	
	■ female/male	

PS/03A	PS/03B
■ 0,7-1,6bar	■ 0,7-1,6bar
■ 1,0-1,6bar	■ 1,0-1,6bar
■ 1,1-1,8bar	■ 1,1-1,8bar
■ 1,6-2,6bar	■ 1,6-2,6bar
■ female/male	■ female/male

RC RUNNING CAPACITOR WITH ROUND SHAPE

MODEL	VOLTAGE	FREQUENCY
8UF	250V/450V	50/60Hz
10UF	250V/450V	50/60Hz
12.5UF	250V/450V	50/60Hz
20UF	250V/450V	50/60Hz
25UF	250V/450V	50/60Hz
30UF	250V/450V	50/60Hz
40UF	250V/450V	50/60Hz
50UF	250V/450V	50/60Hz
60UF	250V/450V	50/60Hz

RG PRESSURE GAUGE

MODEL SIZE	PG-P	PG-SS	PG-S
40mm	PG-P40	PG-SS40	PG-S40
50mm	PG-P50	PG-SS50	PG-S50

- THREE TYPE TYPE SHELL:
(1) PG-P:plastic (2) PG-SS:stainless steel (3) PG-S:steel
- TWO TYPE CONNECTION: BACK/BOTTOM CONNECTION
- THE CONNECTION HAVE TWO TYPE:(1) G1/4" (2) M10 x 1
- FOR 40MM GAUGE, THE SCALE IS 0-6 BAR
- FOR 50MM GAUGE, THE SCALE IS 0-10 BAR OR 0-6 BAR

MS MECHANICAL SEAL

MODEL	SHAFT DIA
MS301-12	12mm
MS301-14	14mm
MS155-15	15mm
MS155-17	17mm
MS155-20	20mm
MS155-22	22mm
MS155-24	24mm

- Graphite to ceramic or graphite to SiC
- stainless steel spring and cover



FLOAT SWITCH

MODEL	VOLTAGE	CURRENT	AMBIENT TEMPERATURE
FLO-1	220-240V	8A	0-80°C
FLO-2	220-240V	8A	0-80°C



FH ANTI VIBRATION FLEXIBLE HOSE WITH ELBOW

MODEL	CONNECTION	LENGTH
Fh50	1"x1"	50cm
Fh60	1"x1"	60cm
Fh100	1"x1"	100cm



FM ANTI VIBRATION FLEXIBLE HOSE WITH ELBOW

MODEL	HOSE	CONNECTIONS	LENGTH
FM-F1"XM1/2" X ø19X35	3/4" gas	1"x1" gas	350mm
FM-F1"XM1/2" X ø19X45	3/4" gas	1"x1" gas	450mm
FM-F1"XM1/2" X ø19X52	3/4" gas	1"x1" gas	520mm
FM-F1" Xø33X52	1" gas	1"x1" gas	520mm
FM-F1" Xø33X58	1" gas	1"x1" gas	580mm
FM-F1" Xø27X60	1" gas	1"x1" gas	600mm
FM-F1/2"XM1/4" Xø13X45	1/2" gas	1"x1" gas	450mm

