



- 24SF, spherical tank
- pressure gauge, back connection
- pressure switch (1.4-2.8bar)
- 3-way connector
- foot valve



- 24CL, cylindrical tank
- pressure gauge, back connection
- pressure switch (1.4-2.8bar)
- 3-way connector
- foot valve
- 1" gas flexible hose



SPHERICAL TANK
(WITH INTERCHANGEABLE MEMBRANE)

MODEL	CONNECTION	MEMBRANE	CAPACITY
ST-24L	1"	For alimentary liquids	24 litres
CT-24L	1"	For alimentary liquids	24 litres
CT-60L	1"	For alimentary liquids	60 litres
CT-100L	1"	For alimentary liquids	100 litres
VT-4L	1"	For alimentary liquids	4 litres
VT-8L	1"	For alimentary liquids	8 litres
VT-16L	1"	For alimentary liquids	16 litres
PT-2L	1 1/4"	For alimentary liquids	2 litres



MODEL	VOLTAGE	FREQUENCY	CURRENT	CONNECTIONS	PROTECTION
PS-01	220-240V 110-115V	50/60Hz	10A	1"x1"	IP 65

Electric device for starting and stopping small single phase pumps, when the tap is opened and closed. It adjusts flow rate and pressure, keeping them constant. This device automatically stops the pump in the absence of water.



MODEL	VOLTAGE	FREQUENCY	CURRENT	CONNECTIONS	PROTECTION
PS-01A	220-240V 110-115V	50/60Hz	10A	1"x1"	IP 65

